



Product Data Sheet

HYDRAULIC OIL HV 15

Product Description:

HYDRAULIC OIL HV 15 is an universal HVI mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

HYDRAULIC OIL HV 15 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance.

- Excellent stability against oxidation.
- High Viscosity Index.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- Very good thermal stability.

HYDRAULIC OIL HV 15 exceeds the following performance criteria:

AFNOR NFE-48-603 ISO 11158 HV DIN 51524/3 HVLP Eaton Vickers M-2950-S/I-386
Sauer Danfoss 520L0463

Property	Unit	Test Method	Typical Value
ISO Grade		ISO 3448	15
Density@15°C	kg/m ³	ASTM D4052	869
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	14.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	3.9
Viscosity Index		ASTM D2270	167
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Water Separability @54°C	Minutes	ASTM D1401	Pass
Demulsibility @54°C	Minutes	ASTM D892	Pass

Product Nr: 4349

Date Issued: 18-08-2014

Date Superseded:

Revision nr: 01